


## SO2-D4 Sulfur Dioxide Sensor - Miniature Size



Dimensions are in millimetres ( $\pm 0.15$  mm).

<b>Performance</b>	Sensitivity	nA/ppm in 10ppm SO <sub>2</sub>	180 to 420
	Response time	t <sub>90</sub> (s) from zero to 10ppm SO <sub>2</sub>	< 15
	Zero current	ppm equivalent in zero air	$\pm 0.7$
	Resolution	RMS noise (ppm equivalent)	< 0.2
	Range	ppm limit of performance warranty	20
	Linearity	ppm error at full scale, linear at zero and 10ppm	< 5
	Overgas limit	maximum ppm for stable response to gas pulse	50
	<b>Lifetime</b>	Zero drift	ppm equivalent change/year in lab air
Sensitivity drift		% change/year in lab air, monthly test	< 6
Operating life		months until 80% original signal (24-month warranted)	> 18
<b>Environmental</b>	Sensitivity @ -20°C	% (output @ -20°C/output @ 20°C) 10ppm	72 to 88
	Sensitivity @ 50°C	% (output @ 50°C/output @ 20°C) 10ppm	74 to 95
	Zero @ -20°C	ppm equivalent change from 20°C	< $\pm 0.5$
	Zero @ 50°C	ppm equivalent change from 20°C	< $\pm 0.5$
<b>Cross Sensitivity</b>	H <sub>2</sub> S sensitivity	% measured gas @ 20ppm	H <sub>2</sub> S < 400
	NO <sub>2</sub> sensitivity	% measured gas @ 10ppm	NO <sub>2</sub> < -120
	Cl <sub>2</sub> sensitivity	% measured gas @ 10ppm	Cl <sub>2</sub> < -60
	NO sensitivity	% measured gas @ 50ppm	NO < 3
	CO sensitivity	% measured gas @ 400ppm	CO < 0.5
	H <sub>2</sub> sensitivity	% measured gas @ 400ppm	H <sub>2</sub> < 0.2
	C <sub>2</sub> H <sub>4</sub> sensitivity	% measured gas @ 400ppm	C <sub>2</sub> H <sub>4</sub> < 15
	NH <sub>3</sub> sensitivity	% measured gas @ 20ppm	NH <sub>3</sub> < 0.1
	CO <sub>2</sub> sensitivity	% measured gas @ 10%	CO <sub>2</sub> < 0.1
<b>Key Specifications</b>	Temperature range	°C	-20 to 50
	Pressure range	kPa	80 to 120
	Humidity range	% rh (see note below)	15 to 90
	Storage period	months @ 3 to 20°C (stored in sealed pot)	6
	Load resistor	$\Omega$ (for optimum performance)	22
	Weight	g	< 2

**Figure 1 Sensitivity Temperature Dependence**




Figure 1 shows the variation in sensitivity caused by changes in temperature.

This data is taken from a typical batch of sensors.

**Figure 2 Zero Temperature Dependence**





Figure 2 shows the variation in zero output caused by changes in temperature, expressed as ppm gas equivalent, referenced to zero at 20°C.

This data is taken from a typical batch of sensors.

**Figure 3 Response to 10ppm SO<sub>2</sub>**



Typical batch of 64 sensors all respond rapidly and repeatably to 10ppm SO<sub>2</sub>.

At the end of the product's life, do not dispose of any electronic sensor, component or instrument in the domestic waste, but contact the instrument manufacturer, Alphasense or its distributor for disposal instructions. NOTE: all sensors are tested at ambient environmental conditions unless otherwise stated. As applications of use are outside our control, the information provided is given without legal responsibility. Customers should test under their own conditions, to ensure that the sensors are suitable for their own requirements.

In the interest of continued product improvement, we reserve the right to change design features and specifications without prior notification. The data contained in this document is for guidance only. Alphasense Ltd accepts no liability for any consequential losses, injury or damage resulting from the use of this document or the information contained within. (©ALPHASENSE LTD) Doc. Ref. SO2-D4/OCT22